



KEIM ECOSIL GRUND

1. Product Information

Keim Ecosil Grund is a silicate based primer coat for interior use.

2. Field Of Application

Keim Ecosil Grund is a base coat to equalise different absorbencies and structures on repaired or filled surfaces, as well as a base coat on plasterboard and sound previously painted surfaces.

3. Product Characteristics

- Equalises surface
- Levels structures
- Good adhesion

Material Data:

Specific Weight	1.370 g/cm ³
Resistance to vapour diffusion	s _d = 0.03 m
Degree of glossiness	matt

Colour Shades:

White

4. Application

Substrate Preparation:

Highly absorbent or friable substrates should firstly be treated with Keim Dilution.

Decoration:

Keim Ecosil Grund can be applied by brush or roller undiluted. Leave for at least 5 hours before over-coating. We do not advise to spray this product.

Air and surface temperature >5°C

Consumption:

Approx. 0.2 lt/m² Keim Ecosil Grund (per coat)

Tools:

Clean immediately after use with water.

5. Packaging

5 & 15 lt containers

6. Storage

Approx. 12 months, if kept cool, but frost free in tightly closed containers.

7. Identification Ref Ordinance Of Dangerous Materials

Not applicable

8. Danger Class In Goodstraffic

Not applicable

9. Product Code

M-SK 01

10. Safety Instructions

Cover surfaces which are not to be painted, in particular glass, natural stone, ceramics etc. Protect the eyes and skin from splashes. Keep out of reach of children.

Refer to COSHH data sheet.