



KEIM FIXATIV

1. Product Information

Keim Fixativ is a silicate binding agent for use with Keim systems. Reacts chemically with the surface.

2. Field Of Application

Binding agent and dust suppressant.

3. Product Characteristics

- Environmentally friendly
- Free from solvents, dilute with water
- Consolidates the surface
- Good surface penetration
- Water vapour permeable
- Odourless
- Non toxic

Material Data:

Density:	Q – 1.17 g/cm _s
Flash Point	non flammable

4. Application

Substrate Preparation:

All surfaces must be thoroughly washed down with clean cold water to remove all surface dirt and dust. When all surfaces are clean, sound, wind dry, dust free and free from all surface contaminants, decoration using Keim Mineral Paints may proceed.

Application:

We would advocate the use of a two coat application of Keim Fixativ, diluted 50:50 with clean cold water and applied by brush, worked well in to the surface leaving a minimum period of 12 hours between coats.

Air and surface temperature >5°C

Consumption:

0.2 lt per square metre for two coats of diluted material

These consumption rates are for guideline purposes. We would recommend that site trials should be conducted should more accurate information be required.

5. Packaging

4 & 24 lt containers

6. Storage

Approx. 12 months if kept cool, away from direct sunlight and in tightly closed containers.

7. Identification Ref. Ordinance Of Dangerous Materials

Not applicable

8. Danger Class In Goods traffic

Not applicable

9. Disposal consideration

Dispose in accordance with current local/national regulations.

10. Safety Instructions

Cover surfaces, which are not to be painted, in particular glass, natural stone, ceramics etc. Spillages and splashes should be washed down with copious amounts of water. Protect the eyes and skin from splashes. Keep out of reach of children.

Refer to COSHH data sheet.