



KEIM I.G. PRIMER (ISOLIERGRUND)

1. Product Information

Keim I.G. Primer is a nitrocollodium, colourless primer with good water vapour permeability used to obliterate staining.

2. Field Of Application

Used as a primer particularly for difficult substrates that are contaminated with soot, nicotine and tar. The substrate should be solid, dry and dust free.

3. Product Characteristics.

- high water vapour permeability
- resistance to yellowing
- Water repellent
- non-brittle
- good adherence

4. Application

Substrate Preparation:

All surfaces should be washed down with clean cold water to remove all surface dirt and dust.

Generally it is sufficient to apply only one coat of Keim I.G. Primer. For extremely strong contamination a second coat is recommended with 4 hours between coats. Keim I.G. Primer should be applied by brush.

Keim I.G. Primer is in a ready to use consistency and can be applied undiluted by brush or roller. After a waiting time of approx. 5 hours Keim I.G. Primer be over coated with Keim Biosil, Quarzil, Concretal and Granital.

Consumption:

Approx. 0.1 lt/m² per coat

Tools:

Clean immediately after use with White spirits.

Temperature:

Do not process below + 40°F (5°C) of re-circulated air and surface.

5. Packaging

5 lt containers

6. Storage

Approx. 12 months, if kept cool but frost free in tightly closed containers. Store dry, do not expose to direct heat.

7. Working Instruction

Do not smoke when processing, do not inhale spray dust. Take precautions that it does not get in to canalisation.

8. Identification Ref Ordinance Of Dangerous Material

Not applicable

9. Danger Class In Goodstraffic

Classification: 3.2

10. Safety Instructions

Cover surfaces which are not to be treated, in particular plants, etc. Protect the eyes and skin from splashes. Keep out of reach of children.

Refer to appropriate COSHH data sheets.