



KEIM I.W. PRIMER (ISOLIERWEISS)

1. Product Information

Keim I.W. Primer is a white pigmented two component sealer on an aqueous base with excellent water vapour permeability. There is a very good compatibility with interior paint systems based on silicates.

Field Of Application:

Keim I.W. Primer is used as an intermediate sealer in case of bleedings (paper and wood dyestuffs) after the first coat, especially for gypsum plasterboard.

2. Product Characteristics.

- high water vapour permeability
- good sealing effect
- solvent free
- good adherence

3. Material Data

Specific weight:	1.11 g/cm
Viscosity:	800 mPas
Diffusion resistance:	sd 0.09 m

4. Application

Substrate Preparation:

All surfaces should be washed down with clean cold water to remove all surface dirt and dust.

Keim I.W. Primer may be applied after the application of the base coat onto partial areas showing bleedings. Generally one coat should be sufficient.

Component A has to be thoroughly mixed with Component B in a ratio of 4:1. Keim I.W. Primer may be applied undiluted by brush or roller. After a waiting period of at least 12 hours Keim I.W. Primer can be coated with Keim Biosil, Quarzil and KEIM Granital etc. If mixed Keim I.W. Primer should be used within 1 day.

Consumption:

Approx. 0.1 lt/m² per coat

Tools:

Clean immediately after use with spirit.

Temperature:

Do not process below + 40°F (5°C) of re-circulated air and surface.

5. Packaging

2 ½ & 10 lt containers

6. Storage

Approx. 6 months, if kept cool but frost free in tightly closed containers. Store dry, do not expose to direct heat.

7. Working Instruction

Do not smoke when processing, do not inhale spray dust. Take precautions that it does not get in to canalisation.

8. Identification Ref Ordinance Of Dangerous Material

Not applicable

9. Safety Instructions

Cover surfaces which are not to be treated, in particular plants, etc. Protect the eyes and skin from splashes. Keep out of reach of children.

Refer to appropriate COSHH data sheets.