



KEIM INNENSPACHTEL

(Keim Interior Filler)

1. Product Information

Keim Innenspachtel is a filler for touching up and smoothing interior surfaces.

2. Field Of Application

Preferably used for treating gypsum plaster boards, sculptor's plaster and lime gypsum plaster.

3. Product Characteristics

Base of binding agent:	gypsum
Shrinkage:	0.05 mm/m
Dry weight:	0.75 g/cm ³

4. Application

Substrate Preparation:

The substrate must be dry and free from release agents. Pre-wet highly absorbent substrates.

Processing:

Water addition is approximately 600 ml/kg. Stir the filler thoroughly. After 3 minutes waiting time the filler is ready to use. Put on a thin layer by spatula or trowel.

Pot Life:	60 minutes
Setting time:	Approx. 60 minutes

Rework:

Can be flatted down when hard.

Subsequent Coats:

Decorate with Keim interior paint systems such as Keim Quarzil, Keim Biosil, Keim Ecosil or Keim Reversil according to the specific working instructions.

Consumption:

Approx. 900 g/m²/mm

Temperatures:

Keim Innenspachtel should only be applied at ambient and substrate temperatures exceeding 5°C.

5. Packing

10 kg bags

6. Storage

Store dry, cool and frost free in closed bags.
Shelf life: 12 months.

7. Identification ref. Ordinance of dangerous material

Not applicable

8. Danger class in goodstraffic

Not applicable

9. Product Code

Not applicable

10. Safety Instructions

Cover surfaces which are not to be treated, in particular glass, natural stone, ceramic, etc. Splashes have to be removed immediately with plenty of water. Protect eyes and skin. Keep out of reach of children.

Observe the actual general rules of building technology. Subject to changes in the interest of product and application improvements. This edition replaces former editions.