



KEIM REVERSIL SCHLAMME

1. Product Information

Slurry base coat for use on historic wall paintings and substrates. Easy to remove.

2. Field Of Application

Keim Reversil Schlamme can be used as a slurry coat to equalise uneven and/or friable substrates. It should be used in conjunction with Keim Reversil to provide a reversible protection layer for historic wall paintings and interior surfaces.

Suitable substrates are plaster, render, sandstone, limestone and sound, stable previous paint layers.

3. Method of Usage

Stir thoroughly and apply undiluted by means of brush or roller.

Only apply as a base coat that is subsequently decorated with Keim Reversil. Leave for a minimum period of 12 hours before overcoating.

Reversil Schlamme may also be mixed with Reversil and applied as a base coat as and when specified.

4. Working Temperature

Do not apply at surface and air temperatures of 5°C or below.

5. Removal

Saturate the surface in question with water for approximately 10 minutes and then carefully scrub off using a soft bristle brush and water.

6. Consumption Rate

Typical consumption rate for a single coat application of Keim Reversil Schlamme onto a normal smooth, dry substrate is 0.5 kg per m². Determine actual consumption rate by means of site trials.

7. Colour

Keim Reversil Schlamme is only supplied in white.

8. Storage

Store cool and free from frost in sealed containers.

Shelf life: 12 months

9. Identification Ref Ordinance Of Dangerous Material

None

10. Danger Class In Goods traffic

None

11. Safety Instructions

Cover surfaces which are not to be painted, in particular glass, natural stone, ceramics etc. Protect the eyes and skin from splashes. Keep out of reach of children.

Refer to appropriate COSHH data sheets.
