



## KEIM GLASSWEAVE ADHESIVE

### 1. Product Information

Solvent free special adhesive for Keim Glassweave wall covering.

### 2. Field Of Application

Keim Glassweave Adhesive is for use with the Keim Glassweave wall covering.

### 3. Product Characteristics

- easy to process paste
- strong adhesion
- Solvent free and odourless
- Suitable for damp rooms
- Damp proof
- sprayable
- transparent

#### **Material Data:**

Specific Weight: 1.1 g/cm<sup>3</sup>  
 Colour: White, dries transparent.

### 4. Application

#### **Substrate Preparation:**

Wall surfaces should be dry, sound and contaminant free. Abrade glossy surfaces to provide a satisfactory key. Highly absorbent surfaces should firstly receive a coat of Keim Dilution.

#### **Application:**

Apply Keim Glassweave Adhesive with a medium pile lambs wool roller (may also be applied by brush and/or spray) in a uniform manner to an area approximately equivalent to 2 fabric widths.

Position the pre-cut fabric edge to edge on the wall. Remove air bubbles using a spatula and press fabric against the wall. In order to obtain uniform surface appearance ensure the same face of the fabric is always positioned uppermost.

Trimming at top and bottom and around doors and other apertures should be done immediately after the fabric has been positioned. Use scissors, or a sharp blade together with a steel ruler.

#### **Temperatures:**

Air and surface temperature >5°C

#### **Decoration:**

Areas that have been covered with Keim Glassweave should be allowed to dry for a minimum period of 12 hours before over-coating. If using Keim Ecosil apply a 2-coat system allowing at least 6 hours between coats.

#### **Consumption:**

0.2 - 0.3 kg/m<sup>2</sup> Keim Glassweave Adhesive depending on pattern.

#### **Tools:**

After use or during breaks clean tools immediately with water.

### 5. Packing

Supplied in 20 kg containers.

### 6. Storage

Approx. 12 months, if kept cool but frost free in tightly closed containers.

### 7. Identification ref. Ordinance of dangerous material

Not applicable

### 8. Danger class in goodstraffic

Not applicable

## 9. Safety Instructions

Cover the surfaces that are not to be treated, in particular glass, natural stone, ceramics, etc. Splashes have to be removed immediately with plenty of water. Protect eyes and skin. Rinse opened eye for several minutes under running water. Avoid inhalation of spraymist. Avoid contamination of sewage systems, watercourses or the environment. Keep out of reach of children.

Observe the actual general rules of building technology. Subject to changes in the interest of product and application improvements. This edition replaces former editions.

