



Safety Data Sheet Issue 01/02

Trade Name: **KEIM I.G. PRIMER**

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Trade name: **KEIM I.G. PRIMER (ISOLIERGRUND)**

Keim I.G. Primer is a liquid blocking primer for use on stained surfaces prior to subsequent decoration.

Manufacturer/importer/distributor:

Keim Mineral Paints Ltd
Muckley Cross
Morville
Nr. Bridgnorth
Shropshire
WV16 4RR

Tel: 01746 714543
Fax: 01746 714526

2. COMPOSITION/INFORMATION ON INGREDIENTS:

Marking in accordance with EU guidelines

EGNR/CAS-NR:	Product	Quantity %'d	R
601-021-00-3/108-88-3	Tolvène	10-25 F, Xn	11-20
603-004-00-6/78-83-1	Butanol	2.5-10 Xn	10-20
607-022-00-5/141-78-6	Ethylacetate	10-25 F	11
607-025-00-1/123-86-4	n-butylacetate	10-25	10
603-002-00-5/64-17-5	Ethanol	2.5-10 F	11
603-117-00-0/67-36-0	2-Propanol, Isopropanol	10-25 F	11
201-557-4/84-74-2	Dibutylthalate	<2.5 Xn	62-6350/53
/108-65-6	1-methoxy-2propylacetat	2.5-10 Xi	10-36

3. HAZARDS IDENTIFICATION

F Highly flammable
Xn dangerous to health
Avoid inhalation

4. FIRST AID MEASURES

General information:

Skin contact: Wash skin thoroughly with soap and water.

Eye contact: Rinse opened eye for at least 10 minutes under running water or with eyewash. Remove any contact lenses. If irritation persists seek medical attention.





Safety Data Sheet Issue 01/02

Trade Name: **KEIM I.G. PRIMER**

Ingestion: Rinse out mouth immediately, drink plenty of water and seek medical advice.

Inhalation: Sit down in a fresh air environment. If dizziness symptoms persist seek medical advice.

5. FIRE-FIGHTING MEASURES

Use foam, water, CO₂ or powder. Keep sealed containers cool with water spray in a fire situation.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: See section 8

Environmental precautions: Avoid contamination of sewage systems, watercourses or the environment.

Methods for cleaning up: Small quantities should be soaked up with sand and removed to waste dumps. Large quantities to be neutralised and removed. Clean with water, not with solvent.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin and eyes. See item 8 for information about suitable protective equipment and technical precautions. Close containers tightly after use. Do not eat or drink when working with the material.

Storage:

Further information about storage:

Store in tightly closed containers, in a cool but frost free environment. Keep away from food, drink and animal feeding stuffs. Protect against heat or direct sunlight

Avoid contamination with incompatible materials. Possibility of electrostatic discharge - risk of fire and/or explosion.

Store according to local and/or national regulation. Storage classification VbF - Class All

8. EXPOSURE CONTROL/PERSONAL PROTECTION

Use in a well ventilated environment

EGNR/CAS-Nr		MAK Value
601-021-00-3/108-88-3	Tolvane	50 ppm
603-004-00-6/78-83-1	Butanol	100 ppm
607-022-00-5/141-78-6	Ethylacetate	400 ppm



