



Safety Data Sheet Issue 02/02

Trade Name: **KEIM B575 E.W. PRIMER**

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Trade name: **KEIM B575 E.W. PRIMER**

Keim B575 E.W. Primer is a primer coat for untreated surfaces used as part of the Keim Anti-graffiti coloured PU system.

Manufacturer/importer/distributor:

Keim Mineral Paints Ltd
Muckley Cross
Morville
Nr. Bridgnorth
Shropshire
WV16 4RR

Tel: 01746 714543

Fax: 01746 714526

2. COMPOSITION/INFORMATION ON INGREDIENTS:

Marking in accordance with EU guidelines

Substance	Content %'d	CAS Number	EG-number	Symbol	Risk Phrases
Epoxyderivaten M<700	>50<100%	25068-38-6		Xi, N	R36/38-51/53-43
Bisfenol-A-Epichloorhydrine; epoxyhars	>10<25%			Xn, N	R36/38-51/53-43

*For full details of R-phrases, see Section 15.

3. HAZARDS IDENTIFICATION

R36/38 Irritating to eyes and skin
R43 May cause sensitisation by skin contact

4. FIRST AID MEASURES

In all cases of doubt, or where symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air, keep patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in the recovery position and seek medical advice.

Eye contact: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water, or use a proprietary skin cleanser. DO NOT use solvents or thinners.

Ingestion: If accidentally swallowed obtain immediate medical attention. Keep at rest. DO NOT induce vomiting.



