



Safety Data Sheet Issue 07/01

Trade Name: **KEIM SILAN PRIMER**

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

Trade name: **KEIM SILAN PRIMER**

Keim Silan Primer is to be used as a hydrophobic impregnation (waterproofing) for mineral building materials such as concrete, render, artificial stones, asbestos cement etc. Use with Keim Granital, Keim Concretal, Keim Concretal Lasur, Keim Contact as a primer coat

Manufacturer/importer/distributor:

Keim Mineral Paints Ltd
Muckley Cross
Morville
Nr. Bridgnorth
Shropshire
WV16 4RR

Tel: 01746 714543
Fax: 01746 714526

2. COMPOSITION/INFORMATION ON INGREDIENTS:

Marking in accordance with EU guidelines

EGNR/CAS-NR:014-007-00-1/17880-47-1.

Triethoxyisobutylsilane	20%	Xi	R 38
-------------------------	-----	----	---------

EGNR/CAS-NR:603-002-00-5/64-17-5

Ethanol	80%	F	11
---------	-----	---	----

3. HAZARDS IDENTIFICATION

Highly flammable; skin irritant

4. FIRST AID MEASURES

General information:

Skin contact: Wash skin thoroughly with soap and water.

Eye contact: Rinse opened eye for at least 10 minutes under running water or with eyewash. Remove any contact lenses. If irritation persists seek medical attention.

Ingestion: Rinse out mouth immediately, drink plenty of water and seek medical advice.

Inhalation: Sit down in a fresh air environment. If dizziness symptoms persist seek medical advice.





Safety Data Sheet Issue 07/01

Trade Name: **KEIM SILAN PRIMER**

5. FIRE-FIGHTING MEASURES

Use foam, water, CO₂ or powder. Keep sealed containers cool with water spray in a fire situation.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: See section 8

Environmental precautions: Avoid contamination of sewage systems, watercourses or the environment.

Methods for cleaning up: Small quantities should be soaked up with sand and removed to waste dumps. Large quantities to be neutralised and removed. Clean with water, not with solvent.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin and eyes. See item 8 for information about suitable protective equipment and technical precautions. Close containers tightly after use.

Storage: **Further information about storage:**
Store in tightly closed containers, in a cool but frost free environment. Keep away from food, drink and animal feeding stuffs. Protect against heat or direct sunlight

Avoid contamination with incompatible materials.

Store according to local and/or national regulation. Storage classification (VCI-system/D): LGK 3.1

8. EXPOSURE CONTROL/PERSONAL PROTECTION

MAK value 1000ppm=1900mg/m³ (ethanol).

Additional information about design of technical systems:

Use in a well ventilated environment

Control methods: Do not open quickly.

Personal protection:-

Eye protection: Avoid direct contact with eyes, wear protective goggles.

Body Protection: After contact with skin wash thoroughly with water



