



# Deslauriers

## T-125 CONCRETE THERMOMETER

- 1" Dial. 5" stem stainless steel construction.
- +/- division 1° increments. Range: +25°F to +125°F.
- Recalibration nut.

**CAT# T125**



## T-550 CONCRETE THERMOMETER

- 1" Dial. 5" stem stainless steel construction.
- +/- division 5° increments. Range: +50°F to +550°F.
- Recalibration nut.

**CAT# T550**



## T-3050 CONCRETE THERMOMETER

- 1-3/4" Dial. 8" stem stainless steel construction.
- +/- division 10° increments. Range: +50°F to +550°F.
- Recalibration nut.

**CAT# T3050**



## MIN MAX THERMOMETER

- Clearly shows minimum and maximum temperature in time period since last setting.
- Has convenient slot on sturdy support board for hanging.
- Resettable high/low indicators.
- Dual scale: -40°F to +120°F; -40°C to +50°C.
- +/- division accuracy, 1° div.

**CAT# MIN/MAX**



## MIN MAX DIGITAL THERMOMETER

Registers maximum and minimum temperatures in both Celsius and Fahrenheit scales. The large display also shows humidity and time.

- +32° F to 122° F (2° div). 0° to 50 °C (1° div)

**CAT# MIN/MAX D**

